THE PATENTED * ORIGINAL!

THE COMPOSITE PALLET

The licensed composite pallets by B & F AG and BFAG.net® Now exclusively available from H.M.R. GmbH






The quickest and safest way to transport fences, feet and accessories.

Upon removal of the first fence panel, all feet become accessible - this saves time and ensures a quick construction.

Guaranteed return on investment by labour cost savings - already after the second assembly and dismantling!

Advantages of the patented composite pallet (CE-certified)

- > Full access to feet and accessories
- > Flat storage on struts prevents the feet catching or falling out
- Deep side pockets on the collapsible fence holders prevent the fence from fanning out or breaking free
- Long side rails provide perfect collision protection and are easily visible to the forklift operator
- > Central supports prevent the feet buckling the first fence



Advantages of the patented collapsible fence holder

- Low transport height due to collapsible fence holders
- > 8 adjustment possibilities make it suitable for all types of fence
- > Self-cleaning fence holder pipes
- Collapsible fence holders are easily interchangeable where special pallets are necessary
- > 30 pallets are only 2.40 m high (corresponds to 3.5 loading metres)



THE PATENTED * ORIGINAL!

Our composite pallets for fences are available in the following models:



Modell KP (Transport width 2.28 m with 2 pallets)

Composite pallet KP - 32 - 6:

- > Length 3.53 m, width 1.14 m for 32 fences and 33 fence feet
- Up to fence length 3.44-3.50 m, horizontal pipes 27 mm, vertical pipes 42 mm
- > Tare 180 kg, gross 1800 kg, minimum fork length for sideways transport 1.00 m, forward transport 2.00 m

Composite pallet KP - 30 - 6:

- > Length 3.53 m, width 1.14 m for 30 fences and 31 fence feet
- Up to fence length 3.44-3.50 m, horizontal pipes 32 mm, vertical pipes 42 mm
- > Tare 179 kg, gross 1800 kg, minimum fork length for sideways transport 1.00 m, forward transport 2.00 m

Composite pallet KP - 26 - 6:

- > Length 3.53 m, width 1.14 m for 26 fences and 27 fence feet
- > Up to fence length 3.44-3.50 m, horizontal pipes 44 mm, vertical pipes 42 mm
- > Tare 178 kg, gross 1800 kg, minimum fork length for sideways transport 1.00 m, forward transport 2.00 m

Modell KP (Transport width 1.96 m with 2 pallets)

Composite pallet KP - 28 - 6:

- > Length 3.53 m, width 0.98 m for 28 fences and 28 fence feet
- > Up to fence length 3.44-3.50 m, horizontal pipes 27 mm, vertical pipes 40 mm
- > Tare 170 kg, gross 1800 kg, minimum fork length for sideways transport 1.00 m, forward transport 2.00 m

Composite pallet KP - 24 - 6:

- > Length 3.53 m, width 0.98 m for 24 fences and 25 fence feet
- > Up to fence length 3.44-3.50 m, horizontal pipes 38 mm, vertical pipes 42 mm
- > Tare 169 kg, gross 1800 kg, minimum fork length for sideways transport 1.00 m, forward transport 2.00 m



Manufacturer: H.M.R. Handels GmbH Gutenbergstraße 1, D-59174 Kamen

Phone: 02307 - 994860 Fax: 02307 - 994862 Email: info@hmr-gmbh.com Website: www.hmr-gmbh.com

last revised: February 2014